

## MODULAR ELEMENTS WITH PORTS A-B



Modular elements CM3F with ports A-B.

- Convert modular interface into threaded ports.
- Maximum flow 40 l/min.
- Threaded ports sizes G3/8"
- Cast iron zinc plated body.


### FEATURES

Max. operating pressure	250 bar
Max. Flow	40 l/min
Hydraulic fluid	DIN 51524 Mineral oils
Fluid viscosity	10 ÷ 500 mm <sup>2</sup> /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level (filter β <sub>25</sub> ≥ 75)	ISO 4406:1999: class 21/19/16 NAS 1638: class 10
Weight	0.54 kg

### HYDRAULIC SYMBOL



### Accessories

 Tightening torque <b>5 Nm</b>	Elements	Code screws (x 4)	Type UNI 5931 - 8.8
	<b>CM3F</b>	<b>Q26074069</b>	M5x35
<b>CM3F + V0800005</b>	<b>Q26074077</b>	M5x80	

3

### ORDERING CODE

<b>CM</b>	Intermediate element
<b>3</b>	Size
<b>F</b>	With ports A-B
<b>**</b>	<b>00</b> = No variant <b>V1</b> = Viton
<b>1</b>	Serial No.

### OVERALL DIMENSIONS

