



## ELECTROMAGNETIC CLUTCH - OIL LUBRICATION



3

### MAXIMUM LOAD ON THE SHAFT



Approximate calculation of drive torque

$$P \text{ (daNm)} = c \cdot p \cdot 0,0017$$

$$P < P_d$$

where:

**p** = pump pressure in BAR

**c** = pump displacement in cc/revolution

from diagram:

**P<sub>d</sub>** = Max. torque allowed by the coupling in daNm


**n** = Motor rotation speed in rpm.

\* Input tension and operating temperature considerably influence the correct operation of the clutch. At temperatures above 70 °C the dynamic torque rating is reduced by 20%. To reach the maximum torque, run the clutch in through repeated working cycles (ON/OFF).

An electromagnetic clutch is a unit designed to convey movement to a UT hydraulic pump through an electrically controlled on/off pulley.

An electromagnetic clutch is composed of:

- an electromagnetic friction clutch (FE)
- an aluminium support (SU) with a conical (AT) and splined (UT) shaft mounted on oil-bath bearings.
- coupling to be ordered separately



### Description

This type of clutch exploits the force of attraction of an electromagnetic field generated by a solenoid that, after being energised (L1 in ON position), connects a pulley to a driving shaft.

The electromagnetic friction clutch is composed of two separate parts:

- a solenoid L1, mounted on the support;
- a pulley PU, mounted on the conical shaft AT.


Operations are as follows:

- under non operating conditions with L1 in OFF position: the pulley, driven by the "V" belt, turns idle on its own bearing,
- under operating conditions with L1 in ON position: the pulley, driven by the "V" belt, conveys movement to the shaft, then to the user UT.


### FEATURES

RPM max	5000 RPM
Static nominal torque (*) (at 12/24V ± 0,5%)	10.2 daNm (pulley Ø152.4 - 2 races) 10.2 daNm (pulley Ø152.4 - 6 races) 12.2 daNm (pulley Ø177.8 - 2 races)
Power supply (*)	12 Vdc - 50W 24 Vdc - 60W
Rotation (pulley side)	CW
Working temperature	-10 °C ÷ +45 °C
Max working temperature coil (*)	100 °C
Oil quantity	0,07 lt.
Type of oil	Type: ISO 19378:2003 Viscosity: ISO VG 150 (ISO 3448:1992)
Oil replacement	After first 500hours then every 12 months

## ORDERING CODE




## SPARE PARTS




Ref.	Code	Q.ty			Description
		IE10..A..	IE10..B..	IE13..C..	
1	34241900	1	1	1	Shaft
2	—	1	1	1	Flanges (sect. 4.02)
3	39042700	1	1	1	Body
4	39101000	1	1	1	Flange D.66/25,4 (only for gr.1)
4	39101200	1	1	1	Flange D.66/36,5 (only for gr.2-3)
5	39204400	1	1	1	Gasket
6	40007300	6	6	6	Screw TCEI M6x20
7	Q27160080	1	1	1	Snap ring 180
8	Q27500070	1	1	1	Key 4x5 DIN 6888
9	44000300	1	1	1	Bearing 600945x75x16
10	44001200	1	1	1	Bearing 6010 50x80x16

Ref.	Code	Q.ty			Description
		IE10..A..	IE10..B..	IE13..C..	
11	44102200	2	2	2	Shaft seal 45x60x7
12	49000100	1	1	1	Washer nylon 13x19x1.5
13	49138600	1	1	1	Plug 1/4"
14	Q26622252	1	1	1	Plug TCEI G1/4
15	46004700	1	—	—	Clutch D.152.4 x 2 - 10 daNm - 12Vdc
	46004800	1	—	—	Clutch D.152.4 x 2 - 10 daNm - 24Vdc
	46008400	—	1	—	Clutch D.152.4 x 6 - 10 daNm - 12Vdc
	46005200	—	—	1	Clutch D.177.8 x 2 - 13 daNm - 12Vdc
	46008200	—	—	1	Clutch D.177.8 x 2 - 13 daNm - 24Vdc
16	26000005	1	—	1	Wire L=65

## ELECTROMAGNETIC CLUTCH - GREASE LUBRICATION



### MAXIMUM LOAD ON THE SHAFT



Approximate calculation of drive torque

$$P \text{ (daNm)} = c \cdot p \cdot 0,0017$$

$$P < P_d$$

where:

**p** = pump pressure in BAR

**c** = pump displacement in cc/revolution

from diagram:

**P<sub>d</sub>** = Max. torque allowed by the coupling in daNm


**n** = Motor rotation speed in rpm.

\* Input tension and operating temperature considerably influence the correct operation of the clutch. At temperatures above 70 °C the dynamic torque rating is reduced by 20%. To reach the maximum torque, run the clutch in through repeated working cycles (ON/OFF).

An electromagnetic clutch is a unit designed to convey movement to a UT hydraulic pump through an electrically controlled on/off pulley.

An electromagnetic clutch is composed of:

- an electromagnetic friction clutch (FE)
- an aluminium support (SU) with a conical (AT) and splined (UT) shaft mounted on grease bearings.
- coupling to be ordered separately



### Description

This type of clutch exploits the force of attraction of an electromagnetic field generated by a solenoid that, after being energised (L1 in ON position), connects a pulley to a driving shaft.

The electromagnetic friction clutch is composed of two separate parts:

- a solenoid L1, mounted on the support;
- a pulley PU, mounted on the conical shaft AT.

Operations are as follows:


- under non operating conditions with L1 in OFF position: the pulley, driven by the "V" belt, turns idle on its own bearing,
- under operating conditions with L1 in ON position: the pulley, driven by the "V" belt, conveys movement to the shaft, then to the user UT.

### FEATURES


RPM max	5000 RPM
Static nominal torque (*)	10.2 daNm (pulley Ø152.4 - 2 races)
	10.2 daNm (pulley Ø152.4 - 6 races)
	12.2 daNm (pulley Ø177.8 - 2 races)
Power supply (*)	12 Vdc - 50W
	24 Vdc - 60W
Rotation (pulley side)	CW
Working temperature	-10 °C ÷ +45 °C
Max working temperature coil (*)	100 °C
Grease quantity	30 gr
Type of grease	DIN 51502 = MPF - 1K-20

## ORDERING CODE

3



## SPARE PARTS







Ref.	Code	Q.ty		Description
		IEG10..A..	IEG10..B..	
1	34202300	1	1	Shaft
2	39017400	1	1	Flange Gr.1-2 (sect 4.02)
3	39021300	1	1	Body
4	39100800	1	1	Flange 44/1
5	39103000	1	1	Spacer
6	39204500	1	1	Gasket
7	40007300	4	4	Screw TCEI M6x20
8	Q26035090	1	1	Screw TEE M8x10
9	Q27150450	1	1	Snap ring E45
10	Q27500070	1	1	Key 4x5 DIN 6888
11	44000300	2	2	Bearing 6009 45x75x16


Ref.	Code	Q.ty		Description
		IEG10..A..	IEG10..B..	
12	44102200	1	1	Shaft seal 45x60x7
13	44102400	1	1	Shaft seal 35x50x7
14	49101000	1	1	Grease nipple
15	Q51437008	1	1	Washer aluminium M8 8.5x15x1.5
16	46004700	1	—	Clutch D.152.4 x 2 - 10 daNm - 12Vdc
	46004800	1	—	Clutch D.152.4 x 2 - 10 daNm - 24Vdc
	46008400	—	1	Clutch D.152.4 x 6 - 10 daNm - 12Vdc
17	26000005	1	—	Wire L=65

# FLANGES IM1 / IE


4

<div data-bbox="558 183 778 224">GR. 1* 1</div>  <div data-bbox="635 638 746 667">* Only for IE</div>	<div data-bbox="1241 183 1461 224">GR. 2-3 2/3</div> 
Spare part flange code 39043000	Spare part flange code 39012500
<div data-bbox="558 750 778 790">SAE/A S/A</div> 	<div data-bbox="1241 750 1461 790">SAE/B S/B</div> 
Spare part flange code 39030600	Spare part flange code 39030800

## FLANGES IEG

<div data-bbox="542 1529 762 1570">GR. 1-2 1/2</div> 	
Spare part flange code 39017400	

## FLANGES IM05

<div data-bbox="1241 1529 1461 1570">GR. 1-2 1/2</div> 	
Spare part flange code 39022800	