

## OUTLET MODULE UNITS



Outlet module units FU3.


- Threaded ports (T) sizes G3/8" or 9/16"-18UNF.
- Outlet modules without ports only for parallel connections
- Maximum flow 40 l/min.
- Aluminum body.

### FEATURES

Max. operating pressure	250 bar
Max. Flow	40 l/min
Hydraulic fluid	DIN 51524 Mineral oils
Fluid viscosity	10 ÷ 500 mm <sup>2</sup> /s
Fluid temperature	-25°C ÷ 75°C
Ambient temperature	-25°C ÷ 60°C
Max. contamination level (filter β <sub>25</sub> ≥ 75)	ISO 4406:1999: class 21/19/16 NAS 1638: class 10
Weight	0.2 kg

1

### HYDRAULIC SYMBOLS



### ORDERING CODE

- |           |  |
|-----------|--|
| <b>FU</b> | Outlet module unit   |
| <b>3</b>  | Size   |
| <b>*</b>  | Port size:<br>For outlet module without ports is not required<br>(only for parallel style)<br><b>1</b> = G3/8"<br><b>2</b> = 9/16"-18UNF |
| <b>00</b> | No variant   |
| <b>2</b>  | Serial No.   |

### OVERALL DIMENSIONS

